

User Manual for Psooo PS-400 Solar Power Bank



Specifications

- Battery: 30000mAh, Li-polymer
- Input ports: microUSB, Type-C
- Output ports: 4 x USB-A
- Input voltage: 2A/5V
- Output voltage: 2,1A/5V
- Solar charging rate: 300mAh/hour
- Certifications: PSE, CE, RoHS, MSDS
- Weight: 681g



- | | |
|------------------------|-------------------|
| 1. Solar panel | 6. Output 2 |
| 2. LED lamp | 7. Type-C input |
| 3. LED power indicator | 8. MicroUSB input |
| 4. On/Off | 9. Output 4 |
| 5. Output 1 | 10. Output 3 |

Instructions

To ensure the stability of the power, please use the standard charger. This power bank uses MicroUSB and Type-C ports to charge itself and USB ports to charge the other devices. For safe charging, please use the USB cable that matches the digital device you want to charge. Slight heating is normal during the charging/discharging of the power bank so it's nothing to think about.

Please store the power bank in a cool and dry place. If it's not going to be used for a longer period of time, please fully charge it once every six months.

To power on the LED lamp, double tap the LED lamp switch while the power bank is in standby mode. Tap the button again to change the light mode, tap it once again and it will enter SOS mode. To turn it off, double tap the button again.